## NSN 5305-00-776-1377

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-776-1377 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.363 inches and 0.413 inches **Fastener Length:** Between 0.451 inches and 0.471 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.223 inches and 0.243 inches Width Between Flats: Between 0.211 inches and 0.219 inches **Extended Washer Diameter:** Between 0.328 inches and 0.338 inches **Extended Washer Thickness:** Between 0.033 inches and 0.043 inches **First Diameter From Head:** Between 0.140 inches and 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.058 inches and 0.088 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-776-1377

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0