NSN 5305-00-776-3889

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-776-3889
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.342 inches and 0.392 inches
Fastener Length:
Between 0.437 inches and 0.457 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.177 inches and 0.197 inches
Width Between Flats:
Between 0.181 inches and 0.189 inches
Extended Washer Diameter:
Between 0.276 inches and 0.286 inches
Extended Washer Thickness:
Between 0.027 inches and 0.037 inches
First Diameter From Head:
Between 0.116 inches and 0.126 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.065 inches and 0.095 inches
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
40
Hardness Rating:
32.0 rockwell c and 36.0 rockwell c
Externally Relieved Body Diameter Quantity:
1
Material:
Steel
Material Specification:
B50r270, fscm 99207 mfr ref single material response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5305-00-776-3889

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0