## NSN 5305-00-778-7828

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-778-7828

View Online at https://aerobasegroup.com/nsn/5305-00-778-7828
Thread Direction:
Right-hand
Thread Length:
Between 0.428 inches and 0.438 inches
Fastener Length:
Between 2.082 inches and 2.092 inches
Head Style:
Dee chamfer
Head Diameter:
0.393 inches
Head Height:
0.205 inches
Distance From Centerline To Flat:
0.149 inches
First Diameter From Head:
Between 0.234 inches and 0.238 inches
Second Diameter From Head:
Between 0.193 inches and 0.201 inches
Third Diameter From Head:
Between 0.235 inches and 0.236 inches
Fourth Diameter From Head:
Between 0.173 inches and 0.181 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.138 inches and 0.178 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.504 inches and 0.520 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
Between 0.543 inches and 0.559 inches
Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
Between 0.583 inches and 0.599 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
6.0 millimeters
Nonstandard Thread Pitch Diameter:
+0.2060 to 0.2160 inches
Thread Pitch In Millimeters:
25.4
Externally Relieved Body Diameter Quantity:
1
Product Name:

**Product Name:** 

Navy special project

## NSN 5305-00-778-7828

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp e9310
Material Specification:
Aisi assn standard single material response
Thread Series Designator:
Si-m
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0