Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-779-7372

| Thread Class: | |
|---|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.813 inches | |
| Fastener Length: | |
| 0.875 inches | |
| Head Style: | |
| Fillister | |
| Head Diameter: | |
| Between 0.250 inches and 0.270 inches | 5 |
| Head Height: | |
| Between 0.102 inches and 0.113 inches | 5 |
| Washer Quantity: | |
| 1 | |
| nternal Drive Style: | |
| Cross recess type 1 | |
| Thread Diameter: | |
| 0.164 inches | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Primary Washer Outside Diameter: | |
| Between 0.243 inches and 0.257 inches | 5 |
| Primary Washer Style: | |
| Split helical ring | |
| Primary Washer Material Thickness: | |
| 0.031 inches | |
| Material: | |
| Steel | |
| Surface Treatment: | |
| Cadmium or zinc | |
| Surface Treatment Specification: | |
| Qq-p-416, type 1, cl 3 federal specificat | tion 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |

NSN 5305-00-779-7372

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

