

View Online at <https://aerobasegroup.com/nsn/5305-00-780-5266>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.195 inches and 0.215 inches

Fastener Length:

Between 1.390 inches and 1.410 inches

Head Style:

Fillister

Head Diameter:

Between 0.292 inches and 0.313 inches

Head Height:

Between 0.089 inches and 0.115 inches

First Diameter From Head:

Between 0.177 inches and 0.183 inches

Second Diameter From Head:

Between 0.145 inches and 0.149 inches

Third Diameter From Head:

Between 0.177 inches and 0.183 inches

Fourth Diameter From Head:

Between 0.145 inches and 0.149 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.978 inches and 1.002 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.010 inches and 1.030 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 1.055 inches and 1.065 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 1.165 inches and 1.195 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

4

Material:

Steel comp 1040 or steel comp 1045

Material Specification:

Astm a108 assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0