NSN 5305-00-780-9352

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-780-9352

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.750 inches
Fastener Length:
2.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height: Between 0.616 inches and 0.625 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon Thread Diameter:
0.625 inches
Width Across Flats:
Between 0.500 inches and 0.505 inches
Hole Quantity:
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
11 Min Tanaila Strangth (nai):
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate

NSN 5305-00-780-9352

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0