NSN 5305-00-786-4028

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-786-4028 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.466 inches and 0.528 inches **Fastener Length:** Between 0.843 inches and 0.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.310 inches and 0.315 inches **Head Height:** Between 0.305 inches and 0.315 inches **Hole Diameter:** 0.068 inches First Diameter From Head: Between 0.185 inches and 0.190 inches **Second Diameter From Head:** Between 0.120 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.212 inches and 0.232 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.357 inches and 0.367 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity:** 2 **Hole Type:** Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Thread Series Designator:**

Unf

NSN 5305-00-786-4028

Externally Relieved Body Screw - Page 2 of 2



Sh	elf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0