NSN 5305-00-790-6770

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-790-6770 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.278 inches **Fastener Length:** Between 1.786 inches and 1.829 inches **Head Style:** Flat chamfer **Head Diameter:** 0.234 inches **Head Height:** Between 0.399 inches and 0.422 inches **First Diameter From Head:** Between 0.116 inches and 0.118 inches **Second Diameter From Head:** 0.234 inches **Third Diameter From Head:** 0.125 inches **Fourth Diameter From Head:** 0.234 inches Fifth Diameter From Head: 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.090 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.277 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 1.529 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

NSN 5305-00-790-6770

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 303
Material Specification:
Qq-s-764 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
580-0025-00, collins radio co. Mfr ref single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0