NSN 5305-00-793-5594

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-793-5594

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.438 inches |
| Fastener Length: |
| 0.438 inches |
| |
| Head Style: |
| Pan Land Biometers |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Locking Feature: |
| Patch threads or strip threads |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Minimum Yield Strength: |
| 85000 pounds per square inch |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5732 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 80205-nas1190 professional/industrial association standard |
| Departure From Cited Designator: |
| As mod by fleet ballistic missile quality as identified by quality control no. Pos0909241 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No. |

NSN 5305-00-793-5594

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0