## NSN 5305-00-795-2488

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-795-2488

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.875 inches   |
| Fastener Length:   |
| 1.125 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| 0.375 inches   |
| Head Height:   |
| 0.250 inches   |
| Hole Diameter:   |
| 0.055 inches   |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.250 inches   |
| Width Across Flats:  |
| 0.188 inches   |
| Hole Quantity:   |
| 4  |
| Hole Type:   |
| Drilled  |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Hardness Rating:   |
| 36.0 rockwell c and 44.0 rockwell c  |
| Hole Configuration Style:  |
| Round internal hexagon   |
| Material:  |
| Steel comp 3135  |
| Material Specification:  |
| Sae assn standard single material response   |
| Surface Treatment:   |
| Cadmium or zinc  |
| Surface Treatment Specification:   |
| Mt-605 fscm 62983 mfr ref single treatment response or mt-611 fscm 62983 mfr ref single treatment response |
| Thread Series Designator:  |

Unf

## NSN 5305-00-795-2488

Socket Head Cap Screw - Page 2 of 2



| _  |    |    |     |      |  |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: |  |
| J. | 16 |    |     | HE.  |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0