NSN 5305-00-795-3027

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-795-3027 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.340 inches **Fastener Length:** 3.230 inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.090 inches **First Diameter From Head:** Between 0.195 inches and 0.200 inches **Second Diameter From Head:** 0.140 inches **Third Diameter From Head:** Between 0.195 inches and 0.200 inches **Fourth Diameter From Head:** 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.160 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.370 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.410 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.890 inches **Internal Drive Style: Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:**

Navy special project

Special Features:

Furnished with one length resin tubing, black, 2.250 in. Lg by 0.250 in. Dia

NSN 5305-00-795-3027

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0