NSN 5305-00-796-9573

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-796-9573 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 1.062 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.312 inches **Head Height:** 0.312 inches **First Diameter From Head:** 0.125 inches **Second Diameter From Head:** 0.250 inches **Third Diameter From Head:** 0.125 inches **Fourth Diameter From Head:** 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.656 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.750 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.812 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 45000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1

Material:

Steel comp 303

NSN 5305-00-796-9573

Externally Relieved Body Screw - Page 2 of 2



Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0