NSN 5305-00-797-8191

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-797-8191 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.172 inches and 0.202 inches **Fastener Length:** 0.582 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** 0.090 inches **First Diameter From Head:** Between 0.104 inches and 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.283 inches and 0.343 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 90 degrees of angle Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-797-8191

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.