NSN 5305-00-800-0318

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-800-0318 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.209 inches |
| Fastener Length: |
| 0.719 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.250 inches and 0.270 inches |
| Head Height: |
| Between 0.091 inches and 0.106 inches |
| First Diameter From Head: |
| 0.125 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.469 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Minimum Yield Strength: |
| 33000 pounds per square inch |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 303se |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-00-800-0318

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0