## NSN 5305-00-800-3445

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-800-3445 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** 0.625 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.373 inches **Head Height:** 0.110 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** 0.146 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.438 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 90.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate** 

Unc

**Thread Series Designator:** 

## NSN 5305-00-800-3445

Externally Relieved Body Screw - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0