NSN 5305-00-800-8427



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-800-8427 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 1.078 inches and 1.109 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 1.234 inches and 1.266 inches **Head Height:** Between 0.359 inches and 0.391 inches **Shoulder Diameter:** 0.625 inches first shoulder **Shoulder Length:** 0.250 inches first shoulder **Point Length:** Between 0.109 inches and 0.141 inches First Diameter From Head: Between 0.229 inches and 0.239 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.578 inches and 0.609 inches **Point Style:** Flat **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 45.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 416 **Material Specification:** Qq-s-764, cond a federal specification single material response

Passivate

Surface Treatment:

NSN 5305-00-800-8427

Thumbscrew - Page 2 of 2



Mil-std-171, finish no.5.4.1, type 3 military standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.