Assembled Washer Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-801-0757

Intead Vass. 2a Thread Direction: Right-hand Thread Length: 0.938 inches Fastener Length: 1.000 inches Head Siyle: Head Siyle: Head Height: 0.190 inches Width Between Flats: 0.375 inches Width Between Flats: 0.375 inches Washer Quantiy: 1 Internal Drive Style: Sid Thread Joineter: 0.250 inches Thread Joineter: 0.250 inches Primary Washer Outside Diameter: 0.250 inches Primary Washer Outside Diameter: 0.250 inches Primary Washer Mustel Thickness: 0.250 inches Primary Washer Matel Thickness: 0.255 inches Primary Washer Matel Thickness: 0.255 inches Primary Washer Matel Thickness: 0.255 inches Material: Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel Steel S	Thread Class:		
Thread Direction:Right-handThread Length:0.938 inchesBastener Length:1.000 inchesHead Style:Head Style:Head NoteHead Height:0.190 inchesVidth Between Flats:0.375 inchesWather Quantity:1Internal Drive Style:StoreNotePrimary Washer Outside Diameter:0.476 inchesPrimary Washer Style:20Primary Washer Style:1StorePrimary Washer Style:20Primary Washer Style:21StorePrimary Washer Style:22Primary Washer Style:2314Primary Washer Style:247 Bin Inchness:0.250 inchesPrimary Washer Style:251 Elai Internal Thickness:0.250 inchesPrimary Washer Style:251 Elai Internal Thickness:0.250 inchesPrimary Washer Style:251 Elai Internal Thickness:0.250 inchesPrimary Washer Style:151 Elai Internal Thickness:0.250 inchesPrimary Washer Style:251 Elai Internal Thickness:0.250 inchesPrimary Washer Style:251 Elai Internal Thickness:0.250 inchesPrimary Washer Style:251 Elai Internal Internal Thickness:0.250 inchesPrimary Washer Style:251 Elai Internal Internal Internal			
Right-hand Unsel 1.000 inches Head Style: O.190 inches Width Between Flats: 0.375 inches Washer Quantity: 1 Interal Drive Style: Stol Thread Diameter: 0.250 inches Thread Valle Por Inch (tpi): 20 Primary Washer Outside Diameter: 0.478 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.025 inches Stel Stel Stel Strates Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.025 inches Stel Stel Strates Primary Washer Style: Flat internal teeth Primary Washer Style: Stel Stel </th <th></th> <th></th> <th></th>			
Thread Length:0.938 inchesFactor Length:1.000 inchesHead Style:Head Style:Head Bight:0.190 inchesWitch Between Flats:0.375 inchesWasher Quantity:11Internal Drive Style:StotPrimary Washer Outside Diameter:0.478 inchesPrimary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Primary Washer Style: <th></th> <th></th> <th></th>			
0.938 inchesFastener Length:1.000 inchesHead Style:Head Reight:0.190 inchesWidth Between Flats:0.375 inchesWasten Quantity:1Internal Drive Style:StotThread Diameter:0.250 inchesPrimary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flatement I Thickness:0.478 inchesPrimary Washer Style:Flatement I Thickness:0.250 inchesPrimary Washer Style:Flatement I Thickness:0.025 inchesMaterial:SteelStateStateStateOutsineInternal LenthPrimary Washer Style:Flatement LenthPrimary Wa			
Fastener Length: 1.000 inches Head Style: Head Style: Head Pagin Head Height: 0.190 inches Width Between Flats: 0.375 inches Washer Quantity: 1 Internal Drive Style: Stot Thread Diameter: 0.250 inches Primary Washer Outside Diameter: 0.476 inches Primary Washer Outside Diameter: 0.478 inches Primary Washer Style: Flat internal teach Primary Washer Material Thickness: 0.025 inches Material: Sted Sted Material: Sted Sted Material: Sted Sted Sted Life: Na Na Sted Life: Na Sted Life: Na Sted Life: Na Sted Life: Na Sted Life: Na			
1000 inchesHead Style:HexagonHead Hoight:0.190 inchesWidth Between Flats:0.375 inchesWasher Quantity:1Internal Drive Style:StotOthes Diameter:0.250 inchesThready Oty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:StelStarface Treatment:CodeliumCadrilumThread Style:StelSterial:NaMaterial:NaInter Thread Style:StelStelStelMaterial:NaNaStel Stel Stel Stel Stel Stel Stel Stel			
Head Style:HexagonHead Height:0.190 inchesWith Between Flats:0.375 inchesWasher Quantity:1Internal Drive Style:StotThread Diameter:0.250 inchesThread Vally Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal tecthPrimary Washer Style:StotStoresMaterial:Outside Diameter:0.25 inchesPrimary Washer Style:Flat internal tecthPrimary Washer Style:CationsOutside Diameter:0.25 inchesBuffer:Naterial:ComparisonCutherPrimary Masher Style:Flat internal tecthPrimary Washer Style:Flat internal tecthPrimary Washer Style:Flat internal tecthPrimary Outside Diameter:Outsin Chrosenter:CutherNaStrater Treatment:CutherNaStrater Teatment:NaNaStrater Teatment:NaNaStrater Teatment:NaNaStrater Teatment:NaNaStrater Teatment:NaStrater Teatment:NaStrater Teatment:NaStrater Teatment:NaStrater Teatme			
HeagonHead Height:0.190 inchesWidth Between Flats:0.375 inchesWasher Quantity:1Internal Drive Style:SlotThread Diameter:0.250 inchesThread Val y Per Inch (tpl):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teathPrimary Washer Style:SlotStoreMaterial:Outside Diameter:0.25 inchesPrimary Washer Style:Flat internal teathPrimary Washer Style:Flat internal teathPrimary Washer Style:CadmiumCadmiumStread Freatment:Cud diameter:NaMaterial:NaStread Style:NaNaNaNaNaStore:NaStore:NaStore:NaStore:NaStore:NaStore:NaNaStore:NaNaNaNaNaNaStore:NaNaStore:NaStore:NaStore:NaStore:Store:Store:Store:Store:Store:Store:Store:			
Head Height:0.190 inchesWith Between Flats:0.375 inchesWasher Quantity:1Interal Drive Style:StotThread Diameter:0.250 inchesThread Quy Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Style:StotStotelStotelPrimary Washer Style:ClatienseOu25 inchesMaterialDiameter:Ou25 inchesPrimary Washer Style:Flat internal teethPrimary Washer Style:ClatienseOu25 inchesMaterial:SteelStefle:CladmiumThread Series Designator:UncStefl Life:NaMaterial:Stefle:NaFlatie:NaStefle:NaStefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle:Stefle: <t< th=""><th></th><th></th><th></th></t<>			
0.190 inchesWidth Between Flats:0.375 inchesWasher Quantity:1Internal Drive Style:SlotThread Dlameter:0.250 inchesThready Qty Per Inch (tpi):20Primary Washer Outside Dlameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:StelStriface Treatment:CodfiniumThread Series Designator:UncShelf Life:NaUnit of Measure:-NaFinal Thicknes:NaDint of Measure:-NaFinitiation:NaStelStelStel SelStel Sel SelStel Sel SelStel Sel SelStel Sel SelStel Sel Sel Sel Sel SelStel Sel Sel Sel Sel Sel Sel Sel Sel Sel S			
Width Between Flats:0.375 inchesWasher Quantity:1Internal Drive Style:SlotThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelStrade Treatment:CardinumThread Series Designator:UncShelf Life:NaUnt Of Measure:-NaFinal Intertion:NaFinal Intertion:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:Shelf Life: </th <th></th> <th></th> <th></th>			
0.375 inchesWasher Quantity:1Internal Drive Style:SlotThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelStrafe Treatment:CadmiunThread Series Designator:UncSheff Life:N/aDit of Measure:Finitarization:NoFig:			
Washer Quantity: 1 Internal Drive Style: Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Primary Washer Outside Diameter: 0.478 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.025 inches Material: Steel Sterel Guridation: Cadmium Thread Series Designator: Unc Sheff Life: N/a Chi Of Measure: - Fomilitarization: No Fig:			
1 Interial Drive Style: Slot Thread Dlameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Primary Washer Outside Dlameter: 0.478 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.025 inches Material: Steel Strafee Treatment: Cadmium Thread Series Designator: Unc Sheft Life: Na Did Measure: Inter Material: Na Did Measure: Inter Masser Fig:			
Interial Drive Style: Stot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Primary Washer Outside Diameter: 0.478 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.250 inches Material: Steel Strafee Treatment: Cadmium Thread Series Designator: Unc Shelf Life: Na Did Measure: Inc Shelf Life: Na Family Intervation: Into Measure: Intomeasure <t< th=""><th></th><th></th><th></th></t<>			
SlotThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelSteelSterlCadmiumThread Series Designator:UncShelf Life:NaUncShelf Life:NaDint of Measure:Int of Measure:Int of Measure:Int of Measure:NaFig:NaFig:			
Irread Diameter:0.250 inchesIrready Qty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelSterlGurinace Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUncShelf Life:N/aFind Masure:Init of Measure:Init of Measure:NoFig:Fig:			
0.250 inchesThready Qty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:NaDid Measure:TFind Measure:TFind Measure:Find Measure:TFind Measure:TFind Measure:Find Measure:Fin			
Thready Qty Per Inch (tpi):20Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aDing Masure:TPamiltarization:TFing:Na			
20 Primary Washer Outside Diameter: 0.478 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.025 inches Material: 0.025 inches Material: 0.025 inches Material: Outsouther Gadmium Thread Series Designator: Unc Shelf Life: N/a Inti Of Measure: Imitarization: No Fine: Na Fine: Imitarization: No Fig:			
Primary Washer Outside Diameter:0.478 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:0.025 inchesSteelStrace Treatment:CadmiumThread Series Designator:UncShelf Life:N/aDint of Measure:Demiltarization:NoFig:			
0.478 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: O.025 inches O.025 inches Katerial: Steel Steel Steel Steres Cadmium Cadmium Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Fmilitarization: No Steel			
Primary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.025 inches0.025 inchesStaterial:SteelStrace Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Denilitarization:NoFig:			
Flat internal teethPrimary Washer Material Thickness:0.025 inchesMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:			
Primary Washer Material Thickness:0.025 inchesMaterial:Material:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:			
0.025 inches Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:			
Material:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnc Of Measure:Demilitarization:NoFig:			
Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Fig:			
Surface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:			
Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:			
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No			
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:			
N/a Unit Of Measure: Demilitarization: No Fiig:			
Unit Of Measure: Demilitarization: No Fiig:			
 Demilitarization: No Fiig:			
No Fiig:	Unit Of Measure:		
No Fiig:			
Fiig:			
A003b0	Fiig:		
	A003b0		