NSN 5305-00-801-2223

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-801-2223 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 1.375 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.625 inches **Head Height:** 0.375 inches **First Diameter From Head:** 0.375 inches **Second Diameter From Head:** 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.063 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.938 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** Cone point 90 degrees of angle Material: Steel comp 303 or steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response

Unc

Thread Series Designator:

NSN 5305-00-801-2223

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-f-14072 spec.