

View Online at <https://aerobasegroup.com/nsn/5305-00-801-4643>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.152 inches and 0.188 inches

**Fastener Length:**

Between 0.156 inches and 0.188 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.156 inches and 0.172 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 302 or steel comp 321 or steel comp 347

**Screw Material Specification:**

Mil-s-7720 military specification 1st material response or mil-s-7720 military specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-7720 spec.