NSN 5305-00-803-2471



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-803-2471 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** 1.150 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response **Screw Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unf **Specification Data:** 80205-nas1403 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

A500d0

No Fiig:

NSN 5305-00-803-2471

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.