

View Online at <https://aerobasegroup.com/nsn/5305-00-803-8218>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.325 inches and 0.375 inches

Fastener Length:

0.375 inches

Head Style:

Fillister

Head Diameter:

Between 0.166 inches and 0.183 inches

Head Height:

Between 0.072 inches and 0.079 inches

Hole Diameter:

0.037 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material Specification:

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 1st material response or q-w -405 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response

Screw Surface Treatment:

Cadmium or zinc

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response

Head Hole Configuration Style:

Round

Thread Series Designator:

Unc

Shelf Life:

Fig:

A500d0