## NSN 5305-00-804-3051

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-804-3051 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.279 inches and 0.309 inches **Fastener Length:** Between 0.378 inches and 0.408 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.269 inches and 0.279 inches **Head Height:** Between 0.040 inches and 0.044 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 4037 **Screw Material Specification:** Mil-s-8695 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-b-416, type 2, cl 3 federal specification all treatment responses **Special Features:** Furnished w/one o ring per mil-p-25732 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-804-3051

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-8695 spec.