NSN 5305-00-805-4253

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-805-4253 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.261 inches and 0.308 inches **Fastener Length:** Between 2.260 inches and 2.277 inches **Head Style: Button Head Diameter:** 0.391 inches **Head Height:** 0.109 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.969 inches and 1.999 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.117 inches first hole **Surface Finish:** 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1 federal specification single treatment response or qq-p-416, type 2 federal specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

NSN 5305-00-805-4253

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0