

View Online at <https://aerobasegroup.com/nsn/5305-00-805-4253>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.261 inches and 0.308 inches

Fastener Length:

Between 2.260 inches and 2.277 inches

Head Style:

Button

Head Diameter:

0.391 inches

Head Height:

0.109 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 1.969 inches and 1.999 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.117 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1 federal specification single treatment response or qq-p-416, type 2 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0