NSN 5305-00-807-9075

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-807-9075 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.296 inches **Fastener Length:** Between 0.406 inches and 0.437 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.275 inches and 0.305 inches **Washer Quantity: Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 28.0 rockwell c and 34.0 rockwell c **Countersink Angle:** 100.0 degrees **Primary Washer Outside Diameter:** Between 0.645 inches and 0.665 inches **Primary Washer Style:** Dome internal teeth **Primary Washer Material Thickness:** 0.017 inches **Secondary Washer Material Thickness:** 0.017 inches Material: Steel comp 1022 or steel comp 1050 **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-807-9075

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0