NSN 5305-00-809-1737

Demilitarization:

No

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-809-1737 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 1.180 inches and 1.187 inches **Head Style:** Flat countersunk **Head Diameter:** 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.920 inches and 0.940 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches grip Material: Steel comp 4340 or steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium or cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 1 federal specification 1st treatment response or qq-p-416 type 2 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

NSN 5305-00-809-1737

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0