Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-811-1033

0-	SS:
2a	
Thread Dire	ection:
Right-hand	
Thread Ler	ngth:
0.375 inche	S
Fastener L	ength:
1.313 inche	S
Head Style	:
Knurled no.	1
Head Diam	eter:
0.750 inche	S
Head Heigh	nt:
0.250 inche	S
First Diame	eter From Head:
0.250 inche	S
Second Dia	ameter From Head:
0.190 inche	S
Distance F	rom Largest Bearing Surface Of Head To End Of First Diameter:
0.437 inche	S
Distance F	rom Largest Bearing Surface Of Head To End Of Second Diameter:
0.937 inche	S
Internal Dri	ive Style:
Slot	
Thread Dia	meter:
0.250 inche	S
Thready Qt	ty Per Inch (tpi):
20	
Externally	Relieved Body Diameter Quantity:
1	
Material:	
Stainless st	eel
Surface Tre	eatment:
Passivate	
Thread Ser	ies Designator:
Unc	
Shelf Life:	
N/a	
	asure:

NSN 5305-00-811-1033

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

