## NSN 5305-00-811-6963

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-811-6963 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.281 inches **Fastener Length:** Between 1.812 inches and 1.828 inches **Head Style:** Fillister **Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** 0.219 inches **First Diameter From Head:** Between 0.266 inches and 0.271 inches **Second Diameter From Head:** Between 0.191 inches and 0.195 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.680 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.531 inches and 1.547 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 30.0 rockwell c and 35.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-811-6963

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0