## NSN 5305-00-812-1632



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-812-1632 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.938 inches and 2.000 inches **Fastener Length:** 2.000 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-8503 military specification 4th material response or mil-s-5626 military specification 5th material response or ams 6300 assn standard 6th material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a

Fiig: A500d0

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5305-00-812-1632

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.