Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-812-2358

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.250 inches	
Fastener Length:	
Between 0.281 inc	nes and 0.312 inches
Head Style:	
Fillister	
Head Diameter:	
Between 0.250 inc	nes and 0.270 inches
Head Height:	
Between 0.102 inc	nes and 0.113 inches
Washer Quantity:	
1	
Internal Drive Sty	e:
Slot	
Thread Diameter:	
0.164 inches	
Thready Qty Per I	nch (tpi):
32	
Primary Washer C	outside Diameter:
Between 0.243 inc	nes and 0.257 inches
Primary Washer S	tyle:
Split helical ring	
Primary Washer N	laterial Thickness:
0.031 inches	
Material:	
Steel comp 1010 fa	stener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastene
or steel comp 1017	fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener
Surface Treatmen	t:
Cadmium or zinc	
Surface Treatmen	t Specification:
Qq-p-416, type 1,	cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series Des	signator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5305-00-812-2358

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

