## NSN 5305-00-812-4361

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-812-4361 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.270 inches **Fastener Length:** Between 0.678 inches and 0.698 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.323 inches and 0.333 inches **Head Height:** Between 0.131 inches and 0.151 inches **First Diameter From Head:** Between 0.158 inches and 0.168 inches **Second Diameter From Head:** Between 0.090 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.020 inches and 0.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.428 inches and 0.448 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-812-4361

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0