
NSN 5305-00-812-9057

Setscrew - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 1.984 inches and 2.016 inches Fastener Length: Between 2.234 inches and 2.266 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.161 inches and 0.170 inches Hole Diameter: 0.062 inches **Point Length:** Between 0.234 inches and 0.266 inches **Point Diameter:** Between 0.180 inches and 0.185 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hole Configuration Style: Round **Point Chamfer Angle:** Between 89.0 degrees and 91.0 degrees Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:**

Passivate

1

NSN 5305-00-812-9057

Setscrew - Page 2 of 2



Surface Treatment Specification:

171, finish no. 5.4.1 military standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0