NSN 5305-00-814-0113

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-814-0113

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.748 inches and 0.875 inches
Fastener Length:
Between 0.859 inches and 0.891 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.429 inches and 0.438 inches
Head Height:
Between 0.306 inches and 0.313 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.218 inches and 0.222 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Material:
Steel
Material Specification:
Fed standard 66 federal standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2 class 3 federal specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
1 type
Departure From Cited Designator:
As modified by head, 45 degv groove around surface of hd, 0.345in.Dia, 0.030in.W
Shelf Life:
N/a

NSN 5305-00-814-0113

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0