

View Online at <https://aerobasegroup.com/nsn/5305-00-814-6913>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.688 inches

Fastener Length:

0.750 inches

Head Style:

Flat chamfer

Head Diameter:

0.750 inches

Head Height:

0.170 inches

Shank Unthreaded Hole Diameter:

0.082 inches first hole

First Diameter From Head:

Between 0.305 inches and 0.315 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.062 inches

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.623 inches first hole and 0.625 inches first hole

Externally Relieved Body Diameter Quantity:

1

Product Name:

Navy special project

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.