

View Online at <https://aerobasegroup.com/nsn/5305-00-814-6913>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.688 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.750 inches

**Head Height:**

0.170 inches

**Shank Unthreaded Hole Diameter:**

0.082 inches first hole

**First Diameter From Head:**

Between 0.305 inches and 0.315 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.062 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.623 inches first hole and 0.625 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Navy special project

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.