

View Online at <https://aerobasegroup.com/nsn/5305-00-815-1819>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.453 inches

**Fastener Length:**

Between 1.626 inches and 1.653 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.767 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037

**Screw Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or ams 6300 assn standard 6th material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Test Data Document:**

76301-macps21201 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

**Mil-std (military Standard):**

Mil-s-5626 spec.