## NSN 5305-00-815-2920

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-815-2920

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.250 inches
Fastener Length:
2.560 inches
Head Style:
Knurled no. 1
Head Diameter:
0.680 inches
Head Height:
0.630 inches
Hole Diameter:
0.072 inches
Point Style:
Flat
Thread Diameter:
0.190 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round
Special Features:
One through hole 0.045 in. Min, 0.050 in. Maximum dia, 0.130 in. From thd end
Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5305-00-815-2920

Thumbscrew - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
i iig.

Mil-std (military Standard):

Mil-s-5002 spec.