# NSN 5305-00-815-2920

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-815-2920

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

1.250 inches

#### Fastener Length:

2.560 inches

#### **Head Style:**

Knurled no. 1

#### Head Diameter:

0.680 inches

#### Head Height:

0.630 inches

#### Hole Diameter:

0.072 inches

# Point Style:

. .....

Flat

#### **Thread Diameter:**

0.190 inches

#### Hole Quantity:

1

#### Hole Type:

Drilled

#### Thready Qty Per Inch (tpi):

32

#### Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

#### Hole Configuration Style:

Round

#### **Special Features:**

One through hole 0.045 in. Min, 0.050 in. Maximum dia, 0.130 in. From thd end

# Material:

Steel comp 630

# Material Specification:

Ams 5643 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

# **Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5305-00-815-2920

Thumbscrew - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.

