NSN 5305-00-815-9965

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-815-9965 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 4.344 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.141 inches and 0.156 inches **Hole Diameter:** 0.047 inches First Diameter From Head: Between 0.159 inches and 0.162 inches **Second Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.844 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity: Hole Type:** Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 30.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Hole Configuration Style:**

Round

Externally Relieved Body Diameter Quantity:

NSN 5305-00-815-9965

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 4640
Material Specification:
Sae assn standard single material response
Surface Treatment:
Cadmium
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0