## NSN 5305-00-816-1716

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-816-1716 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.428 inches and 0.478 inches **Fastener Length:** Between 2.063 inches and 2.093 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.832 inches and 0.890 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1207 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-816-1716

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0