Assembled Washer Screw - Page 1 of 2





Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.298 inches and 0.418 inches

Fastener Length:

0.438 inches

Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

Width Between Flats:

Between 0.305 inches and 0.312 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.365 inches and 0.381 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.020 inches and 0.025 inches

Material:

Steel

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-818-7705

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

