## NSN 5305-00-819-3908

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-819-3908

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.438 inches and 0.500 inches
Fastener Length:
0.500 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:  Between 0.087 inches and 0.097 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 8630
Screw Material Specification:
Mil-s-6050 military specification single material response or an-s-9 military standard single material response
Screw Surface Treatment:
Cadmium or chromium
Screw Surface Treatment Specification:
Qq-p-416 type 2 class 3 federal specification 1st treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A500d0

## NSN 5305-00-819-3908

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.