Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-819-7503

| | ead Class: |
|------|--|
| 2a | |
| Thr | read Direction: |
| Rig | ht-hand |
| | read Length: |
| 0.2 | 50 inches |
| Fas | stener Length: |
| 0.2 | 50 inches |
| Hea | ad Style: |
| Flat | countersunk |
| Hea | ad Diameter: |
| Bet | ween 0.249 inches and 0.279 inches |
| Inte | ernal Drive Style: |
| Cro | ss recess type 1 |
| Thr | ead Diameter: |
| 0.13 | 38 inches |
| Thr | eady Qty Per Inch (tpi): |
| 32 | |
| Cou | untersink Angle: |
| 100 | 0.0 degrees |
| Mat | terial: |
| Ste | el comp 430 |
| Mat | terial Specification: |
| Qq- | s-763 federal specification single material response |
| Sur | face Treatment: |
| Pas | ssivate |
| Thr | ead Series Designator: |
| Und | |
| She | elf Life: |
| N/a | |
| Uni | t Of Measure: |
| | |
| Der | nilitarization: |
| No | |
| Fiig | j: |
| ۵۵۵ |)3b0 |