## NSN 5305-00-820-4531

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-820-4531 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.430 inches **Fastener Length:** 0.870 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.557 inches and 0.570 inches **Head Height:** 0.440 inches **First Diameter From Head:** Between 0.295 inches and 0.306 inches **Second Diameter From Head:** Between 0.177 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.060 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.440 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

## NSN 5305-00-820-4531

Externally Relieved Body Screw - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0