

View Online at <https://aerobasegroup.com/nsn/5305-00-820-6356>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.211 inches

Fastener Length:

0.312 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.072 inches and 0.082 inches

Washer Quantity:

2

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

45.0 rockwell c secondary washer and 53.0 rockwell c secondary washer

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.250 inches

Secondary Washer Outside Diameter:

0.258 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.031 inches

Secondary Washer Material Thickness:

0.016 inches

Special Features:

Lockwasher and washer not rated screw 55000 poundsper square inch

Material:

Steel comp 1010 or steel or steel comp 1020 or steel comp 1025

Material Specification:

Qq-s-634 federal specification 1st material response or 66, 1060-1080 federal standard 2nd material response or qq-s-636 federal specification 2nd material response or mil-s-7952 military specification 3rd material response or mil-s-7952 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.