

View Online at <https://aerobasegroup.com/nsn/5305-00-820-6356>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.211 inches

**Fastener Length:**

0.312 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.072 inches and 0.082 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

45.0 rockwell c secondary washer and 53.0 rockwell c secondary washer

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.250 inches

**Secondary Washer Outside Diameter:**

0.258 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.031 inches

**Secondary Washer Material Thickness:**

0.016 inches

**Special Features:**

Lockwasher and washer not rated screw 55000 poundsper square inch

**Material:**

Steel comp 1010 or steel or steel comp 1020 or steel comp 1025

**Material Specification:**

Qq-s-634 federal specification 1st material response or 66, 1060-1080 federal standard 2nd material response or qq-s-636 federal specification 2nd material response or mil-s-7952 military specification 3rd material response or mil-s-7952 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas720 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-7952 spec.