NSN 5305-00-820-7607

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-820-7607

| Thread Class: |
|---------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.625 inches |
| Fastener Length: |
| 1.625 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.625 inches and 0.635 inches |
| Shoulder Diameter: |
| 0.4358 inches first shoulder and 0.4367 inches first shoulder |
| Shoulder Length: |
| 0.875 inches first shoulder |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel comp 4140 |
| Surface Treatment: |
| Cadmium |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |