

View Online at <https://aerobasegroup.com/nsn/5305-00-821-3869>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.000 inches and 1.188 inches

**Fastener Length:**

Between 1.688 inches and 1.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**End Application:**

Mrap-rg-33 and rg-33 auv; mrap - cougar; mrap buffalo mk2a2

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel

**Material Specification:**

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 type 2 sc 3 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0