## NSN 5305-00-822-2873

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-822-2873 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.927 inches and 0.994 inches **Fastener Length:** Between 1.749 inches and 1.796 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.262 inches and 1.272 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Screw Material:** Steel comp 4140 or steel comp 8740 or steel comp 3140 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or qq-s-624 federal specification 3rd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification single treatment response **Shank Surface Finish:** 32.0 microinches **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-822-2873

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.