NSN 5305-00-822-3628

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-822-3628 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.273 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.490 inches and 0.518 inches **Head Height:** Between 0.201 inches and 0.211 inches **First Diameter From Head:** 0.312 inches **Second Diameter From Head:** 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.312 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 304 **Material Specification:** Qq-s-763 cond a federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:**

NSN 5305-00-822-3628

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0